

Features


- High speed switching
- VCEO(sus)=400V
- Suitable for Switching Regulator and Motor Control

Ordering Information

Type NO.	Marking	Package Code
STD13005FC	STD13005	TO-220F-3SL

Outline Dimensions

unit : mm



Absolute maximum ratings

(Tc=25°C)

Characteristic	Symbol	Ratings	Unit
Collector-Base voltage	V _{CBO}	700	V
Collector-Emitter voltage	V _{CEO}	400	V
Emitter-base voltage	V _{EBO}	9	V
Collector current (DC)	I _C	4	A
Collector current (Pulse)	I _{CM}	8	A
Base current (DC)	I _B	2	A
Base current (Pulse)	I _{BM}	4	A
Total Power dissipation (Tc=25°C)	P _D	30	W
Junction temperature	T _j	150	°C
Storage temperature	T _{stg}	-55~150	°C

Electrical Characteristics

(Tc=25°C)

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Collector-Emitter sustaining voltage	V _{CE(sus)}	I _C =10mA, I _B =0	400	-	-	V
Collector cut-off current	I _{CEV}	V _{CEV} =Rated Value V _{BE(off)} =1.5V	-	-	1	mA
Emitter cut-off current	I _{EBO}	V _{EB} =9V, I _C =0	-	-	1	mA
DC Current gain	h _{FE} *	I _C =1A, V _{CE} =5V	10	-	60	
		I _C =2A, V _{CE} =5V	8	-	40	
Collector-Emitter saturation voltage	V _{CE(sat)} *	I _C =1A, I _B =0.2A	-	-	0.5	V
		I _C =2A, I _B =0.5A	-	-	0.6	
		I _C =4A, I _B =1A	-	-	1	
Base-Emitter saturation voltage	V _{BE(sat)} *	I _C =1A, I _B =0.2A	-	-	1.2	V
		I _C =2A, I _B =0.5A	-	-	1.6	
Transition frequency	f _T	V _{CB} =10V, I _C =0.5A, f=1MHz	4	-	-	MHz
Output capacitance	C _{ob}	V _{CB} =10V, I _E =0, f=0.1MHz	-	65	-	pF
Turn on Time	t _{ON}	V _{CC} =125V, I _C =2A, R _L =62.5Ω I _{B1} =-I _{B2} =0.4A	-	-	0.8	μs
Storage Time	t _{STG}		-	-	4	
Fall Time	t _F		-	-	0.9	

* Pulse test: PW ≤ 300 μs, Duty cycle ≤ 2% Pulse

Electrical Characteristic Curves

Fig. 1 $P_D - T_C$




Fig. 2 $V_{BE(sat)}, V_{CE(sat)} - I_C$




Fig. 3 $h_{FE} - I_C$




Fig. 4 Turn off time




Fig. 5 Turn on time




Fig. 6 Capacitance





Fig. 7 Safe Operating Area



These AUK Corp. products are intended for usage in general electronic equipment (Office and communication equipment, measuring equipment, domestic electrification, etc.) Please make sure that you consult with us before you use these AUK products in equipments which require high quality and/or reliability, and in equipments which could have major impact to the welfare of human life(atomic energy control, airplane, spaceship, traffic signal, combustion central, all types of safety device, etc.) AUK cannot accept liability to any damage which may occur in case these AUK products were used in the mentioned equipments without prior consultation