

**Descriptions**

The S78xx series are three-terminal positive regulators providing over 1A output current with internal current limiting, thermal shutdown and safe area protection. These regulators are useful in a wide range of applications. Although they are just fixed voltage regulators, the S78xx series can be used with external components to obtain adjustable voltages and currents.

**Features**

- Output Current of 1A
- Short Circuit Current Limit Protection
- Thermal Shutdown Protection
- Output Transistor Safe Area Protection

**Ordering Information**

Type NO.	Marking	Package Code
S78xxPIC	S78□□PI	TO-220F-3SL

□□: Voltage Code (05:5V, 06:6V, 08:8V, 09:9V, 10:10V, 12:12V, 15:15V, 24:24V)

**Outline Dimensions** (Unit : mm )

**BLOCK DIAGRAM**

**PIN Connections**

1. Input
2. GND
3. Output

**Absolute Maximum Ratings**

Ta=25°C

Characteristic	Symbol	Rating	Unit
Input voltage	V <sub>I</sub>	40 (S7824PIC)	V
		35 (ALL Others)	V
Power dissipation	P <sub>D</sub>	2.0	W
Junction temperature	T <sub>J</sub>	150	°C
Storage temperature range	T <sub>stg</sub>	-55 ~ +150	°C

**Device Selection Guide**

Device	Output Voltage
S7805PIC	5V
S7806PIC	6V
S7808PIC	8V
S7809PIC	9V
S7810PIC	10V
S7812PIC	12V
S7815PIC	15V
S7824PIC	24V

## Electrical Characteristics

(Electrical Characteristics at  $0^{\circ}\text{C} \leq T_J \leq 125^{\circ}\text{C}$  and  $V_I = 10\text{V}$ ,  $I_O = 500\text{ mA}$ , Unless otherwise specified)

Characteristic	Symbol	Test Condition*		S7805PIC			Unit
				Min.	Typ.	Max.	
Output Voltage**	$V_O$		$T_J = 25^{\circ}\text{C}$	4.80	5.0	5.20	V
		$I_O = 5\text{ mA} \sim 1000\text{ mA}$ $V_I = 7.0\text{V} \sim 20\text{V}$	$0^{\circ}\text{C} \leq T_J \leq 125^{\circ}\text{C}$	4.75	5.0	5.25	
Line Regulation	$\Delta V_{O(\Delta V_I)}$	$V_I = 7.0\text{V} \sim 25\text{V}$	$T_J = 25^{\circ}\text{C}$	-	3	100	mV
		$V_I = 8.0\text{V} \sim 12\text{V}$		-	1	50	
Load Regulation	$\Delta V_{O(\Delta I_L)}$	$I_O = 5\text{ mA} \sim 1000\text{ mA}$	$T_J = 25^{\circ}\text{C}$	-	15	100	mV
		$I_O = 250\text{ mA} \sim 750\text{ mA}$		-	5	50	
Quiescent Current	$I_{QC}$		$T_J = 25^{\circ}\text{C}$	-	4.2	8.0	mA
Quiescent Current Change	$\Delta I_{QC}$	$V_I = 7.0\text{V} \sim 25\text{V}$	$0^{\circ}\text{C} \leq T_J \leq 125^{\circ}\text{C}$	-	-	1.3	mA
		$I_O = 5\text{ mA} \sim 1000\text{ mA}$		-	-	0.5	
Dropout Voltage	$V_{DROD}$	$I_O = 1000\text{ mA}$	$T_J = 25^{\circ}\text{C}$	-	2.0	-	V
Ripple Rejection	RR	$f = 120\text{ Hz}$ $V_I = 8.0\text{V} \sim 18\text{V}$	$0^{\circ}\text{C} \leq T_J \leq 125^{\circ}\text{C}$	62	78	-	dB
Short-Circuit Current Limit	$I_{SO}$		$T_J = 25^{\circ}\text{C}$	-	0.75	-	A

\* Pulse testing techniques are used to maintain the junction temperature as close to the ambient temperature as possible. Thermal effects must be taken into separately.

\*\* This specification applies only for dc power dissipation permitted by absolute maximum ratings.

## Electrical Characteristics

(Electrical Characteristics at  $0^{\circ}\text{C} \leq T_J \leq 125^{\circ}\text{C}$  and  $V_I = 11\text{V}$ ,  $I_O = 500\text{ mA}$ , Unless otherwise specified)

Characteristic	Symbol	Test Condition*		S7806PIC			Unit
				Min.	Typ.	Max.	
Output Voltage**	$V_O$		$T_J = 25^{\circ}\text{C}$	5.75	6	6.25	V
		$I_O = 5\text{ mA} \sim 1000\text{ mA}$ $V_I = 8.0\text{V} \sim 21\text{V}$	$0^{\circ}\text{C} \leq T_J \leq 125^{\circ}\text{C}$	5.70	6	6.30	
Line Regulation	$\Delta V_{O(\Delta V_I)}$	$V_I = 8.0\text{V} \sim 25\text{V}$	$T_J = 25^{\circ}\text{C}$	-	5	120	mV
		$V_I = 9.0\text{V} \sim 13\text{V}$		-	1.5	60	
Load Regulation	$\Delta V_{O(\Delta I_L)}$	$I_O = 5\text{ mA} \sim 1000\text{ mA}$	$T_J = 25^{\circ}\text{C}$	-	14	120	mV
		$I_O = 250\text{ mA} \sim 750\text{ mA}$		-	4	60	
Quiescent Current	$I_{QC}$		$T_J = 25^{\circ}\text{C}$	-	4.3	8	mA
Quiescent Current Change	$\Delta I_{QC}$	$V_I = 8.0\text{V} \sim 25\text{V}$	$0^{\circ}\text{C} \leq T_J \leq 125^{\circ}\text{C}$	-	-	1.3	mA
		$I_O = 5\text{ mA} \sim 1000\text{ mA}$		-	-	0.5	
Dropout Voltage	$V_{DROD}$	$I_O = 1000\text{ mA}$	$T_J = 25^{\circ}\text{C}$	-	2.0	-	V
Ripple Rejection	RR	$f = 120\text{ Hz}$ $V_I = 9.0\text{V} \sim 19\text{V}$	$0^{\circ}\text{C} \leq T_J \leq 125^{\circ}\text{C}$	59	75	-	dB
Short-Circuit Current Limit	$I_{SO}$		$T_J = 25^{\circ}\text{C}$	-	0.55	-	A

\* Pulse testing techniques are used to maintain the junction temperature as close to the ambient temperature as possible. Thermal effects must be taken into separately.

\*\* This specification applies only for dc power dissipation permitted by absolute maximum ratings.

## Electrical Characteristics

(Electrical Characteristics at  $0^{\circ}\text{C} \leq T_J \leq 125^{\circ}\text{C}$  and  $V_I = 14\text{V}$ ,  $I_O = 500\text{ mA}$ , Unless otherwise specified)

Characteristic	Symbol	Test Condition*		S7808PIC			Unit
				Min.	Typ.	Max.	
Output Voltage**	$V_O$		$T_J = 25^{\circ}\text{C}$	7.70	8	8.30	V
		$I_O = 5\text{ mA} \sim 1000\text{ mA}$ $V_I = 10.5\text{V} \sim 23\text{V}$	$0^{\circ}\text{C} \leq T_J \leq 125^{\circ}\text{C}$	7.60	8	8.40	
Line Regulation	$\Delta V_{O(\Delta V_I)}$	$V_I = 10.5\text{V} \sim 25\text{V}$	$T_J = 25^{\circ}\text{C}$	-	6	160	mV
		$V_I = 11\text{V} \sim 17\text{V}$		-	2	80	
Load Regulation	$\Delta V_{O(\Delta I_L)}$	$I_O = 5\text{ mA} \sim 1000\text{ mA}$	$T_J = 25^{\circ}\text{C}$	-	12	160	mV
		$I_O = 250\text{ mA} \sim 750\text{ mA}$		-	4	80	
Quiescent Current	$I_{QC}$		$T_J = 25^{\circ}\text{C}$	-	4.3	8	mA
Quiescent Current Change	$\Delta I_{QC}$	$V_I = 10.5\text{V} \sim 25\text{V}$	$0^{\circ}\text{C} \leq T_J \leq 125^{\circ}\text{C}$	-	-	1	mA
		$I_O = 5\text{ mA} \sim 1000\text{ mA}$		-	-	0.5	
Dropout Voltage	$V_{DROD}$	$I_O = 1000\text{ mA}$	$T_J = 25^{\circ}\text{C}$	-	2.0	-	V
Ripple Rejection	RR	$f = 120\text{ Hz}$ $V_I = 11.5\text{V} \sim 21.5\text{V}$	$0^{\circ}\text{C} \leq T_J \leq 125^{\circ}\text{C}$	55	72	-	dB
Short-Circuit Current Limit	$I_{SO}$		$T_J = 25^{\circ}\text{C}$	-	0.45	-	A

\* Pulse testing techniques are used to maintain the junction temperature as close to the ambient temperature as possible. Thermal effects must be taken into separately.

\*\* This specification applies only for dc power dissipation permitted by absolute maximum ratings.

## Electrical Characteristics

(Electrical Characteristics at  $0^{\circ}\text{C} \leq T_J \leq 125^{\circ}\text{C}$  and  $V_I = 16\text{V}$ ,  $I_O = 500\text{ mA}$ , Unless otherwise specified)

Characteristic	Symbol	Test Condition*		S7809PIC			Unit
				Min.	Typ.	Max.	
Output Voltage**	$V_O$		$T_J = 25^{\circ}\text{C}$	8.65	9	9.35	V
		$I_O = 5\text{ mA} \sim 1000\text{ mA}$ $V_I = 11.5\text{V} \sim 24\text{V}$	$0^{\circ}\text{C} \leq T_J \leq 125^{\circ}\text{C}$	8.55	9	9.45	
Line Regulation	$\Delta V_{O(\Delta V_I)}$	$V_I = 11.5\text{V} \sim 27\text{V}$	$T_J = 25^{\circ}\text{C}$	-	7	180	mV
		$V_I = 13\text{V} \sim 19\text{V}$		-	2	90	
Load Regulation	$\Delta V_{O(\Delta I_L)}$	$I_O = 5\text{ mA} \sim 1000\text{ mA}$	$T_J = 25^{\circ}\text{C}$	-	12	180	mV
		$I_O = 250\text{ mA} \sim 750\text{ mA}$		-	4	90	
Quiescent Current	$I_{QC}$		$T_J = 25^{\circ}\text{C}$	-	4.3	8	mA
Quiescent Current Change	$\Delta I_{QC}$	$V_I = 11.5\text{V} \sim 27\text{V}$	$0^{\circ}\text{C} \leq T_J \leq 125^{\circ}\text{C}$	-	-	1	mA
		$I_O = 5\text{ mA} \sim 1000\text{ mA}$		-	-	0.5	
Dropout Voltage	$V_{DROD}$	$I_O = 1000\text{ mA}$	$T_J = 25^{\circ}\text{C}$	-	2.0	-	V
Ripple Rejection	RR	$f = 120\text{ Hz}$ $V_I = 12\text{V} \sim 22\text{V}$	$0^{\circ}\text{C} \leq T_J \leq 125^{\circ}\text{C}$	55	70	-	dB
Short-Circuit Current Limit	$I_{SO}$		$T_J = 25^{\circ}\text{C}$	-	0.4	-	A

\* Pulse testing techniques are used to maintain the junction temperature as close to the ambient temperature as possible. Thermal effects must be taken into separately.

\*\* This specification applies only for dc power dissipation permitted by absolute maximum ratings.

## Electrical Characteristics

(Electrical Characteristics at  $0^{\circ}\text{C} \leq T_J \leq 125^{\circ}\text{C}$  and  $V_I = 17\text{V}$ ,  $I_O = 500\text{ mA}$ , Unless otherwise specified)

Characteristic	Symbol	Test Condition*		S7810PIC			Unit
				Min.	Typ.	Max.	
Output Voltage**	$V_O$		$T_J = 25^{\circ}\text{C}$	9.60	10	10.4	V
		$I_O = 5\text{ mA} \sim 1000\text{ mA}$ $V_I = 12.5\text{V} \sim 25\text{V}$	$0^{\circ}\text{C} \leq T_J \leq 125^{\circ}\text{C}$	9.50	10	10.5	
Line Regulation	$\Delta V_{O(\Delta V_I)}$	$V_I = 12.5\text{V} \sim 28\text{V}$	$T_J = 25^{\circ}\text{C}$	-	7	200	mV
		$V_I = 14\text{V} \sim 20\text{V}$		-	2	100	
Load Regulation	$\Delta V_{O(\Delta I_L)}$	$I_O = 5\text{ mA} \sim 1000\text{ mA}$	$T_J = 25^{\circ}\text{C}$	-	12	200	mV
		$I_O = 250\text{ mA} \sim 750\text{ mA}$		-	4	100	
Quiescent Current	$I_{QC}$		$T_J = 25^{\circ}\text{C}$	-	4.3	8	mA
Quiescent Current Change	$\Delta I_{QC}$	$V_I = 12.5\text{V} \sim 28\text{V}$	$0^{\circ}\text{C} \leq T_J \leq 125^{\circ}\text{C}$	-	-	1	mA
		$I_O = 5\text{ mA} \sim 1000\text{ mA}$		-	-	0.5	
Dropout Voltage	$V_{DROD}$	$I_O = 1000\text{ mA}$	$T_J = 25^{\circ}\text{C}$	-	2.0	-	V
Ripple Rejection	RR	$f = 120\text{ Hz}$ $V_I = 13\text{V} \sim 23\text{V}$	$0^{\circ}\text{C} \leq T_J \leq 125^{\circ}\text{C}$	55	71	-	dB
Short-Circuit Current Limit	$I_{SO}$		$T_J = 25^{\circ}\text{C}$	-	0.4	-	A

\* Pulse testing techniques are used to maintain the junction temperature as close to the ambient temperature as possible. Thermal effects must be taken into separately.

\*\* This specification applies only for dc power dissipation permitted by absolute maximum ratings.

## Electrical Characteristics

(Electrical Characteristics at  $0^{\circ}\text{C} \leq T_J \leq 125^{\circ}\text{C}$  and  $V_I = 19\text{V}$ ,  $I_O = 500\text{ mA}$ , Unless otherwise specified)

Characteristic	Symbol	Test Condition*		S7812PIC			Unit
				Min.	Typ.	Max.	
Output Voltage**	$V_O$		$T_J = 25^{\circ}\text{C}$	11.5	12	12.5	V
		$I_O = 5\text{ mA} \sim 1000\text{ mA}$ $V_I = 14.5\text{V} \sim 27\text{V}$	$0^{\circ}\text{C} \leq T_J \leq 125^{\circ}\text{C}$	11.4	12	12.6	
Line Regulation	$\Delta V_{O(\Delta V_I)}$	$V_I = 14.5\text{V} \sim 30\text{V}$	$T_J = 25^{\circ}\text{C}$	-	10	240	mV
		$V_I = 16\text{V} \sim 22\text{V}$		-	3	120	
Load Regulation	$\Delta V_{O(\Delta I_L)}$	$I_O = 5\text{ mA} \sim 1000\text{ mA}$	$T_J = 25^{\circ}\text{C}$	-	12	240	mV
		$I_O = 250\text{ mA} \sim 750\text{ mA}$		-	4	120	
Quiescent Current	$I_{QC}$		$T_J = 25^{\circ}\text{C}$	-	4.3	8	mA
Quiescent Current Change	$\Delta I_{QC}$	$V_I = 14.5\text{V} \sim 30\text{V}$	$0^{\circ}\text{C} \leq T_J \leq 125^{\circ}\text{C}$	-	-	1	mA
		$I_O = 5\text{ mA} \sim 1000\text{ mA}$		-	-	0.5	
Dropout Voltage	$V_{DROD}$	$I_O = 1000\text{ mA}$	$T_J = 25^{\circ}\text{C}$	-	2.0	-	V
Ripple Rejection	RR	$f = 120\text{ Hz}$ $V_I = 15\text{V} \sim 25\text{V}$	$0^{\circ}\text{C} \leq T_J \leq 125^{\circ}\text{C}$	55	71	-	dB
Short-Circuit Current Limit	$I_{SO}$		$T_J = 25^{\circ}\text{C}$	-	0.35	-	A

\* Pulse testing techniques are used to maintain the junction temperature as close to the ambient temperature as possible. Thermal effects must be taken into separately.

\*\* This specification applies only for dc power dissipation permitted by absolute maximum ratings.

## Electrical Characteristics

(Electrical Characteristics at  $0^{\circ}\text{C} \leq T_J \leq 125^{\circ}\text{C}$  and  $V_I = 23\text{V}$ ,  $I_O = 500\text{ mA}$ , Unless otherwise specified)

Characteristic	Symbol	Test Condition*		S7815PIC			Unit
				Min.	Typ.	Max.	
Output Voltage**	$V_O$		$T_J = 25^{\circ}\text{C}$	14.40	15	15.60	V
		$I_O = 5\text{ mA} \sim 1000\text{ mA}$ $V_I = 17.5\text{V} \sim 30\text{V}$	$0^{\circ}\text{C} \leq T_J \leq 125^{\circ}\text{C}$	14.25	15	15.75	
Line Regulation	$\Delta V_{O(\Delta V_I)}$	$V_I = 17.5\text{V} \sim 30\text{V}$	$T_J = 25^{\circ}\text{C}$	-	12	300	mV
		$V_I = 20\text{V} \sim 26\text{V}$		-	3	150	
Load Regulation	$\Delta V_{O(\Delta I_L)}$	$I_O = 5\text{ mA} \sim 1000\text{ mA}$	$T_J = 25^{\circ}\text{C}$	-	12	300	mV
		$I_O = 250\text{ mA} \sim 750\text{ mA}$		-	4	150	
Quiescent Current	$I_{QC}$		$T_J = 25^{\circ}\text{C}$	-	4.3	8	mA
Quiescent Current Change	$\Delta I_{QC}$	$V_I = 17.5\text{V} \sim 30\text{V}$	$0^{\circ}\text{C} \leq T_J \leq 125^{\circ}\text{C}$	-	-	1	mA
		$I_O = 5\text{ mA} \sim 1000\text{ mA}$		-	-	0.5	
Dropout Voltage	$V_{DROD}$	$I_O = 1000\text{ mA}$	$T_J = 25^{\circ}\text{C}$	-	2.0	-	V
Ripple Rejection Ratio	RR	$f = 120\text{ Hz}$ $V_I = 18.5\text{V} \sim 28.5\text{V}$	$0^{\circ}\text{C} \leq T_J \leq 125^{\circ}\text{C}$	54	70		dB
Short-Circuit Current Limit	$I_{SO}$		$T_J = 25^{\circ}\text{C}$	-	0.23	-	A

\* Pulse testing techniques are used to maintain the junction temperature as close to the ambient temperature as possible. Thermal effects must be taken into separately.

\*\* This specification applies only for dc power dissipation permitted by absolute maximum ratings.

## Electrical Characteristics

(Electrical Characteristics at  $0^{\circ}\text{C} \leq T_J \leq 125^{\circ}\text{C}$  and  $V_I = 33\text{V}$ ,  $I_O = 500\text{ mA}$ , Unless otherwise specified)

Characteristic	Symbol	Test Condition*		S7824PIC			Unit
				Min.	Typ.	Max.	
Output Voltage**	$V_O$		$T_J = 25^{\circ}\text{C}$	23.0	24	25.0	V
		$I_O = 5\text{ mA} \sim 1000\text{ mA}$ $V_I = 27\text{V} \sim 38\text{V}$	$0^{\circ}\text{C} \leq T_J \leq 125^{\circ}\text{C}$	22.8	24	25.2	
Line Regulation	$\Delta V_{O(\Delta V_I)}$	$V_I = 27\text{V} \sim 38\text{V}$	$T_J = 25^{\circ}\text{C}$	-	18	480	mV
		$V_I = 30\text{V} \sim 36\text{V}$		-	6	240	
Load Regulation	$\Delta V_{O(\Delta I_L)}$	$I_O = 5\text{ mA} \sim 1000\text{ mA}$	$T_J = 25^{\circ}\text{C}$	-	12	480	mV
		$I_O = 250\text{ mA} \sim 750\text{ mA}$		-	4	240	
Quiescent Current	$I_{QC}$		$T_J = 25^{\circ}\text{C}$	-	4.6	8	mA
Quiescent Current Change	$\Delta I_{QC}$	$V_I = 27\text{V} \sim 38\text{V}$	$0^{\circ}\text{C} \leq T_J \leq 125^{\circ}\text{C}$	-	-	1	mA
		$I_O = 5\text{ mA} \sim 1000\text{ mA}$		-	-	0.5	
Dropout Voltage	$V_{DROD}$	$I_O = 1000\text{ mA}$	$T_J = 25^{\circ}\text{C}$	-	2.0	-	V
Ripple Rejection Ratio	RR	$f = 120\text{ Hz}$ $V_I = 28\text{V} \sim 38\text{V}$	$0^{\circ}\text{C} \leq T_J \leq 125^{\circ}\text{C}$	50	66	-	dB
Short-Circuit Current Limit	$I_{SO}$		$T_J = 25^{\circ}\text{C}$	-	0.15	-	A

\* Pulse testing techniques are used to maintain the junction temperature as close to the ambient temperature as possible. Thermal effects must be taken into separately.

\*\* This specification applies only for dc power dissipation permitted by absolute maximum ratings.

Electrical Characteristic Curves (Continue)

Fig. 1  $V_O$  vs.  $V_I$




Fig. 2  $I_{QC}$  vs.  $V_I$




Fig. 3  $V_O$  vs.  $T_J$




Fig. 4  $I_{QC}$  vs.  $T_J$




Fig. 5  $V_{DROP}$  vs.  $T_J$







Fig. 6  $V_O$  vs.  $I_O$




**Fig. 7 R.R vs. I<sub>o</sub>**



**Fig. 8 I<sub>SO</sub> vs. V<sub>i</sub>**



**Fig. 9 P<sub>D</sub> vs. T<sub>a</sub>**



**These AUK Corp. products are intended for usage in general electronic equipment (Office and communication equipment, measuring equipment, domestic electrification, etc.) Please make sure that you consult with us before you use these AUK products in equipments which require high quality and/or reliability, and in equipments which could have major impact to the welfare of human life(atomic energy control, airplane, spaceship, traffic signal, combustion central, all types of safety device, etc.) AUK cannot accept liability to any damage which may occur in case these AUK products were used in the mentioned equipments without prior consultation**